

YZ-H761

羟基丙烯酸树脂

特性

- 1、施工性好
- 2、丰满度，表面效果佳
- 3、光泽以及漆膜通透性高
- 4、耐候性优异

用途

应用于中高档汽车修补罩光清漆以及 2K 色漆。

性质

特性	数值	单位
组份	丙烯酸共聚物	
外观	清澈透明	
固体份	75±2	%
黏度	5000-8000	mPa.s/25°C
酸值	6-10	mgKOH/g
溶剂	XYL/BAC	
色号	≤1(Fe-Co)	
羟基含量	3.0(固体份)	%

储存说明

- 远离热及火源，置于阴凉通风处，容器保持紧密。
- 本产品自生产日起，保质期限为 12 个月。

包装规格

200kg/桶

安全

本产品含溶剂，必须做好防护措施，小心操作，避免接触皮肤与眼睛，其它详细资料请参考物质安全说明书。

以上资料系经试验所得，仅供参考，不作任何保证之用。鉴于树脂功能的局限性及用户要求的多样性，若使用本公司产品，使用前请按自身的要求严格试验树脂的适应性及最终产品的稳定性。

版本：2024-4-27

YZ-H761

Hydroxyl Acrylic Resins

Characteristics

- 1、 Good constructability
- 2、 Fullness, good surface effect
- 3、 High gloss and permeability of paint film
- 4、 Excellent weather resistance

Application

Applied to middle and high-end automobile repair finish varnish and 2K color paint.

Property

Characteristics	Numeric value	Unit
Component	Acrylic copolymer	
Appearance	Clear and bright	
Solid Content	75±2	%
Viscosity	5000-8000	mPa.s/25°C
Acid Value	6-10	mgKOH/g
Solvent	XYL/BAC	
Color	≤1(Fe-Co)	
OH Content	3.0	%

Storage instructions

- Keep away from fire and heat, placed in a cool and ventilated place, Keep the container tightly sealed.
- Shelf time:12 months.

Packing

200Kg/Bucket

Safety

This product contains solvent, you must take protective measures , avoid contacting with skin and eyes, other information please refer to the material safety instruction.

The above information is obtained through experiments. It is provided for reference only. Given the limitations of resin functionality and the diversity of user requirements.If you use our products, please strictly verify according to your own requirements .Please strictly test the adaptability of the resin and the stability of the final product according to your own requirements.

Version: 2024-3-15

Jiafu Industrial Zone Yinshan Industrial Park high-tech zone Qingyuan City Guangdong Province China

Tel: 0763-3607328 E-mail: liushul@yakoo.com.cn [Http://www.yakoo.com.cn](http://www.yakoo.com.cn)